

AMT 5 MKII

CEILING SPEAKER



Elements	5" full range Woofer
Rated Power	3W /6W (100V)
Sensitivity (1W/1m)	89 dB
Frequency Response	90 Hz - 16kHz
Dimensions	Ø 184 mm
Hole for mounting	Ø 165 mm
Material	Metal (grille) ABS (enclosure)

Specifications are subjects to be change without notice



AMT 6 MKII

CEILING SPEAKER



Elements	6.5" full range Wbfer
Rated Power	5W / 10W (100V)
Sensitivity (1W/1m)	92 dB
Frequency Response	130 Hz - 15kHz
Dimensions	Ø 190 mm
Hole for mounting	Ø 175 mm
Material	Metal (grille) ABS (enclosure)

Specifications are subjects to be change without notice



AMT 5 MKII

ALTAVOZ DE TECHO



Elementos	Woofer todo rango 5"
Potencia soportada	3W / 6W (100V)
Sensibilidad (1W/1m)	89 dB
Respuesta en frecuencia	90 Hz - 20kHz
Dimensiones	Ø 184 mm
Diámetro de montaje	Ø 165 mm
Material	Metal (rejilla) ABS (recinto)

Especificaciones sujetas a cambios sin previo aviso



AMT 6 MKII

ALTAVOZ DE TECHO



Elementos	Woofer todo rango 6.5"
Potencia soportada	5W/ 10W (100V)
Sensibilidad (1W/1m)	92 dB
Respuesta en Frecuencia	130 Hz - 15kHz
Dimensiones	Ø 190 mm
Diámetro de montaje	Ø 175 mm
Material	Metal (rejilla) ABS (recinto)

Especificaciones sujetas a cambios sin previo aviso

