



DYNAMIC PROFESSIONAL MICROPHONE SERIES

Congratulations on your purchase of **MARK** series professional meeting microphone. This series of microphones are designed by using advanced suppressive circuit and excellent professional cartridge, which make the microphones have the features of super uni-directional, high sensitivity and good frequency response, they are perfectly in place on the occasions of media interviewing, conference, speech, stage, filming and TV performance.

TECHNICAL DATA	DM 44	DM 46	DM 50
Element	Dynamic	Dynamic	Dynamic
Polar Pattern	Uni-directional	Uni-directional	Uni-directional
Frequency Response	70 Hz - 13kHz	70 Hz - 13kHz	70 Hz - 13kHz
Sensitivity	-73dB +/-3dB (0dB=1V/Pa at 1kHz)	-73dB +/-3dB (0dB=1V/Pa at 1kHz)	-73dB +/-3dB (0dB=1V/Pa at 1kHz)
Impedance	600Ω	600Ω	600Ω
Accessories	3x mic holders, transport case	mic holder, XLR3M/XLR3F cable (5m), transport case	mic holder, XLR3M/XLR3F cable (5m), foldable stand

TECHNICAL DATA	DM 56	DM 66
Element	Dynamic	Dynamic
Polar Pattern	Uni-directional	Uni-directional
Frequency Response	60 Hz - 14kHz	50 Hz - 15kHz
Sensitivity	-73dB +/-3dB (0dB=1V/Pa at 1kHz)	-75dB +/-3dB (0dB=1V/Pa at 1kHz)
Impedance	600Ω	250Ω
Accessories	mic holder, XLR3M/XLR3F cable (5m), transport case	mic holder, XLR3M/XLR3F cable (5m), transport case

CAUTIONS:

1. If used indoors, the microphone should not be faced to the speaker, at the same time, please adjust the volume of the amplifier unit there is no acoustic howling.
2. If the microphone will not be used for a period, please remove the battery, so as to avoid the corrosion caused by battery leakage.



SERIE DE MICROFONOS PROFESIONALES DINAMICOS

Felicidades por la adquisición de este micrófono de la serie  **MARK** profesional. Esta serie de micrófonos, está diseñada usando un avanzado circuito supresor y una cápsula de condensador profesional lo que le hace tener todas las características super uni-direccional, alta sensibilidad y buena respuesta en frecuencia, son pues, adecuados para entrevistas, conferencias, discursos, escenarios o platós de

DATOS TECNICOS	DM 44	DM 46	DM 50
Elemento	Dinamico	Dinamico	Dinamico
Patrón Polar	Unidireccional	Unidireccional	Unidireccional
Resp. en frecuencia	70 Hz - 13kHz	70 Hz - 13kHz	70 Hz - 13kHz
Sensibilidad	-73dB +/-3dB (0dB=1V/Pa a 1kHz)	-73dB +/-3dB (0dB=1V/Pa a 1kHz)	-73dB +/-3dB (0dB=1V/Pa a 1kHz)
Impedancia	600Ω	600Ω	600Ω
Accesorios	3x soporte micro, estuche	soporte micro, cable (5m) XLR3M/XLR3F, estuche	soporte micro,cable (5m) XLR3M/ XLR3F, soporte desplegable

DATOS TECNICOS	DM 56	DM 66
Elemento	Dinamico	Dinamic
Patrón Polar	Unidireccional	Unidireccional
Resp. en frecuencia	60 Hz - 14kHz	50 Hz - 15kHz
Sensibilidad	-73dB +/-3dB (0dB=1V/Pa a 1kHz)	-75dB +/-3dB (0dB=1V/Pa a 1kHz)
Impedancia	600Ω	250Ω
Accesorios	soporte micro, cable (5m) XLR3M/XLR3F, estuche	soporte micro, cable (5m) XLR3M/XLR3F, estuche

PRECAUCIONES:

1. Si utiliza el micrófono en interior, no debe encarar el micro a los altavoces, ajuste el volumen del amplificador hasta que no haya acople.
2. Si no va a usar el micrófono durante un tiempo prolongado de tiempo, retire las pilas para evitar la corrosión provocada por el desgaste total de la pila.